

DECLARATION OF PERFORMANCE

No 02/2 UKCA/Bla/01

1. **THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** Dry pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Annex G, Bla Group, unglazed (UGL); polished
2. **INTENDED USE OR USES:** For walls and floors internal and for walls external, in buildings and industrial facilities.
3. **MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
4. **SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
5. **HARMONIZED STANDARD:** EN 14411:2012
6. **DECLARED PERFORMANCE:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
Reaction-to-fire performance	A1 / A1 _{FL} Classified Without Testing (CWT)
Release of dangerous substances:	
- Cadmium	$\leq 0,07 \text{ mg/dm}^2$
- Lead	$\leq 0,8 \text{ mg/dm}^2$
Breaking strength:	
- thickness <7,5mm	$\geq 700 \text{ N}$
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	$\geq 0,5 \text{ N/mm}^2$
- dispersion adhesives	$\geq 1 \text{ N/mm}^2$
- reaction resin adhesives	$\geq 2 \text{ N/mm}^2$
- mortar	NPD
Slippage according to CEN/TS 16165:2012, Annex B	NPD - No Performance Determined
Thermal shock resistance	Pas
Durability for:	
- internal use:	Pass
- external use: resistance to freeze-thaw cycles	Pass
Tactility	NPD

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the product(s) identified above is/are in conformity with the declared performance in the table above. This Declaration Of Performance is issued under the sole responsibility of the manufacturer identified above.

Place, date:
Kielce, 01.04.2022

Signed on behalf of the manufacturer

QUALITY DIRECTOR
CERSANIT S.A.

Jolanta Grzebna