

DECLARATION OF PERFORMANCE NO 08CPR/Bib/RO/03

- The unique identification code of the product type: **08/Bib/GL/RO**
- Intended use or use:
Dry-pressed ceramic tiles with water absorption equal to $0.5\% < E \leq 3\%$; Annex H; Bib group, glazed (GL), glinker; for interior and exterior walls and floors of buildings - as described on the packaging.
- Manufacturer: **ROVESE S.A.; AL. Solidarności 36; 25-323 Kielce**
- System(s) of assessment and verification of constancy of performance: **SYSTEM 4**
- Harmonised standard: **EN 14411:2012**
- Declared performance:

<i>Essential characteristics</i>	<i>Performance (level and/or class)</i>	<i>Harmonised technical specification</i>
Reaction-to-fire performance	A1 _{FL}	Classified Without Testing (CWT) EN 14411:2012
Release of dangerous substances:		
- Cadmium	Max 0,07mg/mm ²	
- Lead	Max 0,8mg/mm ²	
Breaking strength:		
- thickness ≥ 7.5 mm	≥ 1100 N	
- thickness < 7.5 mm	≥ 700 N	
Bond strength/adhesion [N/mm²]:		
- cementitious adhesives	NPD - No Performance Determined	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Slippage according to DIN 51130	According to the packaging	
Thermal shock resistance	Meets	
Durability for:		
- internal use:	Meets	
- external use: resistance to freeze-thaw cycles	Meets	
Tactility	NPD - No Performance Determined	

A copy of the Declaration of Performance is available on the website: www.rovese.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

Kielce, 01.01.2017
(place and date of issue)

.....
(signature)